



EG2500DC/EG2500DDC

- Rated power of 2000 watt, 110/220/230/240V
- Eagle's commercial-grade OHV engine
- 12V direct current output
- Automatic voltage regulation by AVR
- Low oil level automatic protection
- Current overcurrent protection
- Capacious fuel tank of 18 liter, for which to run 15 hours constantly
- Frame-type safety generator support
- Wheel components are optional
- Self-starting or remote-starting is optional.



Engine model	G200F/G200FD
Engine type	Single cylinder,4stroke, forced cooling ,OHV
Power output	4.1Kw/3600rpm
Bore×Stroke	68mm×54mm (2.7"×2.1")
Displacement	196cc
Compression ratio	8.5:1
Oil capacity	0.6L (0.16gal)
Fuel tank capacity	15L (4.0gal)
Fuel consumption	≤395g/Kw.h
Continuing time	12h
Rated frequency	50 Hz/60 Hz
Rated voltage	110V/115V/120V/220V/ 230V/240
Voltage regulator system	Automatic Voltage Regulation
Rated output	2.0Kw
Max output	2.2Kw
Power factor	1.0
Charging voltage	12V(DC)
Charging current	8.3A(DC)
Starting system	Recoil start/Electric-start
Ignition system	Transistorized magneto ignition
Noise (≤7m)	≤75dB(A)
Dimension	590×475×460 (23.2"×22.6"×18.1")
Net weight	43Kg (94.8lb)

Options:

- ☆ Fuel tank, recoil starter colors and types
- ☆ Voltage meter indicator type or digital type
- ☆ Wheel kit
- ☆ Intelligent Self-start or remote start



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae