

SILENT TYPE AIR COOLED DIESEL GENERATOR

| Model | | HG6500SE3 | |
|--------------------------|-------------------------------|--|---------------|
| Generator Sets | Frequency (HZ) | 50HZ | 60HZ |
| | Max.output (KW) | 5.0 | 5.5 |
| | Rated output(KW) | 4.6 | 5 |
| | Rated AC Voltage (V) | 400/230V | |
| | Power Factor | 1 | |
| | DC output | 12V / 8.3A | |
| | Phase | Three Phase | |
| | Alternator Type | Self-excited,2-pole, Three phase alternator(brush or brushless) | |
| | Starting System | Electric | |
| | Noise Level (Dba/7m) | 68-72Dba | |
| | Fuel Tank Capacity (L) | 12.5L | |
| | Continues Running Time (hr) | 7hr | |
| Engine | Engine Model | HR186FA | |
| | Engine Type | single-cylinder, vertical,4-stroke air-cooled diesel engine | |
| | Max output of engine | 8.5HP/3000rpm | 9.2HP/3600rpm |
| | Bore × Stroke (mm) | 86×72 | |
| | Displacement Capacity(cc) | 411cc | |
| | Fuel consumption rate(g/kw.h) | ≤280 | |
| | Fuel | 0# or -10# light diesel oil | |
| | Lubrication Oil Volume (L) | 1.65L | |
| | Combustion System | Direct Injection | |
| Standard Features | Voltmeter | Yes | |
| | AC Output Socket | 2 | |
| | AC Circuit Breaker | Yes | |
| | Oil warning Light | Yes | |
| | Oil Alert | Yes | |
| | 22AH battery | Yes | |
| | DC circuit breaker | Yes | |
| | Hour Meter | Optional | |
| | Three Phase Voltage | Optional | |
| | Current Meter | Optional | |

| | | |
|--------------------------|-----------------------|-------------|
| Optional Features | Remote Control | Optional |
| | ATS | Optional |
| | 30AH battery | Optional |
| | 36AH battery | Optional |
| | Digital Control Panel | Optional |
| | New Canopy Type | Optional |
| | Welding(20-160A) | Optional |
| Dimensions | LxWxH (mm) | 960x555x780 |
| | Net Weight(kgs) | 172 |
| | 20FT Load Quantity | 72PCS |

NEW CANOPY TYPE



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae

