



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae

LG12000-1

- Rated power of 10 kw (50HZ) , 380/400/415V
- Loncin's powerful commercial-grade V-twin 678CC engine
- 12V direct-current output
- Automatic voltage regulator (AVR) to automatically regulate voltage
- Lower oil level automatic protection
- Current over-current protection
- Equipped with extra large oil tank for long working time
- Frame-type generator support for overall protection
- Having suitable and convenient storage battery and moving wheels



| | | | | |
|--------------------|---|-------------|-------|-------|
| Model | EG12000-1 | | | |
| Engine model | EG2V78FD-1 | | | |
| Engine type | Air-cooled,4-stroke,ohv90L,V-twin cylinders | | | |
| Bore×Stroke | 78mm×71mm (3.0"×2.8") | | | |
| Displacement | 678cc | | | |
| Oil capacity | 1.6L (0.42gal) /filter replacement | | | |
| Ignition system | Transistorized magneto | | | |
| Starting system | Electric start | | | |
| Volts DC/DC | 12V/8.3A | | | |
| Rated frequency | 50 Hz/ 60 Hz | | | |
| Rated voltage | 220 V/230 V/240 V | 380 V/400 V | | |
| | 50 Hz | 60 Hz | 50 Hz | 60 Hz |
| Rated output | 3.Kw | 3.5Kw | 9Kw | 10Kw |
| Max power | 3.2Kw | 3.8Kw | 10Kw | 11Kw |
| Fuel tank capacity | 25L (6.6gal) | | | |
| Continuing | / | | | |
| Dimension | 868×635×676 (34.2"×25"×26.6") | | | |
| | (Height at 786 if with wheel kit) | | | |
| Net weight | 160Kg (353lb) | | | |

EG12000

- Rated power of 8500 watt (50HZ) , 220/230/240V
- Eagle's powerful commercial-grade V-twin 678CC engine
- 12V direct-current output
- Automatic voltage regulator (AVR) to automatically regulate voltage
- Lower oil level automatic protection
- Current over-current protection
- Equipped with extra large oil tank for long working time
- Frame-type generator support for overall protection
- Having suitable and convenient storage battery and moving wheels

| | |
|--------------------|---|
| Model | EG12000 |
| Engine model | EG2V78FD-1 |
| Engine type | Air-cooled,4-stroke,ohv90L,V-twin cylinders |
| Bore×Stroke | 78mm×71mm (3.0"×2.8") |
| Displacement | 678cc |
| Oil capacity | 1.6L (0.42gal) /filter replacement |
| Ignition system | Transistorized magneto |
| Starting system | Electric start |
| Volts DC/DC | 12V/8.3A |
| Rated frequency | 50 Hz/ 60 Hz |
| Rated voltage | 220 V/230 V/240 V |
| Rated output | 8.5Kw/9.5Kw 3.5Kw |
| Max power | 9.5Kw/10.5Kw 3.8Kw |
| Fuel tank capacity | 25L (6.6gal) |
| Continuing | / |
| Dimension | 868×635×676 (34.2"×25"×26.6") (786Height at 786 if with wheel kit) |
| Net weight | 160Kg (353lb) |