

VIBRATION RAMMERS

FEATURES

- Clean design, compact and light weight.
- Direct drive with centrifugal clutch ensures maximum safety and efficiency.
- Fully automatic lubrication. Hermetically sealed to guarantee long life with minimum maintenance.
- VIBRAR, high tensile steel with good quality castings are all produced by the factory to ensure the finest engineering standards.

SPECIFICATIONS

| Model | | PRD-70B | PRD-80B | PRD-80 |
|-------------|--|---|---|---|
| Weight (kg) | | 70 | 78 | 77 |
| Size | Dimensions HxWxL (mm) | 1,010x430x690 | 1,050x445x690 | 1,070x430x740 |
| | Ramming Shoe WxL (mm) | 280x330 | 300x335 | 300x330 |
| Performance | Number of Impacts (/min.) | 450~650 | 550~650 | 450~650 |
| | Impact Stroke (mm) | 40~60 | 40~50 | 40~61 |
| | Lubrication | Oil spray circulating | Oil spray circulating | Oil spray circulating |
| Engine | Model | Robin EH12-2D (4-cycle) HONDA GX120K1AR (4-cycle) YANMAR L48N6 diesel | Robin EH12-2D (4-cycle) HONDA GX120K1AR (4-cycle) YANMAR L48N6 diesel | Robin EH12-2D (4-cycle) HONDA GX120K1AR (4-cycle) YANMAR L48N6 diesel |
| | Max. Horsepower (Hp/rpm) | 2.5~3.0/3,600 | 2.5~3.0/3,600 | 2.5~3.0/3,600 |
| | Fuel (ratio of gasoline & lubrication oil) | Gasoline/Diesel | Gasoline/Diesel | Gasoline/Diesel |
| | Fuel Tank Capacity (ℓ) | 1.5 | 1.5 | 1.9 |
| | Starting System | Recoil starter | Recoil starter | Recoil starter |
| | Transmission | Direct coupled with Centrifugal Clutch | Direct coupled with Centrifugal Clutch | Direct coupled with Centrifugal Clutch |

POWER TROWELS

SPECIFICATIONS

| Model | Blade Size (mm) | Blade No. | Weight (kg) | Size (mm) | R.P.M | Engine (Hp/rpm) |
|--------|-----------------|-----------|-------------|-----------------|--------|----------------------------------|
| PT-75 | 310x150x1.6 | 3 | 45 | 1,800x750x650 | 50-125 | Robin EX13 3.0/3,600 |
| PT-90 | 310x150x1.6 | 4 | 60 | 2,000x900x700 | 50-125 | Robin EX17, EY203D 3.5-4.0/3,600 |
| PT-100 | 330x160x1.8 | 4 | 70 | 2,100x1,000x700 | 50-125 | Robin EX17, EY203D 3.5-4.0/3,600 |