




For Agriculture & Garben

Hoping for an abundant crop ...

HIDELS PUMPS

SE Series



SE-50X, SE-80X, SE-100X (in Yellow Frame also)

Strong & Durable Robin Engine

- Highly effective mechanical seal made with special carbon ceramics provides extra durability.
- Entire unit is protected by sturdy rollover pipe frame.
- Strong and lightweight die-cast aluminum pump.

Applications

- Sprinkling for field irrigation.
- Irrigation of paddy fields.
- Orchard cultivation.
- Pumping water from wells.
- Feeding or draining water to/from ponds or troughs.
- Feeding or draining water on fish farms.
- Washing cattle, barns or agricultural tools.
- Feeding water into water reservoirs.

Specifications

	Model	SE-50X	SE-80X	SE-100X
P U M P	Connection Dia	50 mm (2")	80 mm (3")	100 mm (4")
	Connection Thread	Outer Pipe Thread		
	Total Head	30 m (98 ft)	26 m (85 ft)	28 m (92 ft)
	Delivery Volume	600 L/min (158 USG/min)	930 L/min (246 USG/min)	1450 L/min (383 USG/min)

	Max. Suction Head	8 m (26 ft)			
E N G I N E	Type	Forced Air-cooled 4-stroke Gasoline Engine			
	Model	Robin EY15-3D	Robin EY20-3D	Robin EY28-3D	
	Exhaust Volume	143 cc	183 cc	273cc	
	Output	Rated Power	2.0 kW (2.7 PS) / 3600 rpm	2.6 kW (3.5 PS) / 3600 rpm	4.0 kW (5.5 PS) / 3600 rpm
		Max. Power	2.6 kW (3.5 PS) / 4000 rpm	3.7 kW (5.0 PS) / 4000 rpm	5.5 kW (7.5 PS) / 4000 rpm
	Fuel	Automotive Unleaded Gasoline			
	Fuel Tank Capacity	2.8 L	3.8 L	5.5L	
	Continuous Operating Time	Approx. 2 hrs 40 min	Approx. 3 hrs		
	Starting Method	Recoil Starter			
	Standard Accessories	1 Strainer, 2 Hose Couplings, 3 Hose Bands, 1 Engine Tool Set			
Gross Weight	23 kg	34 kg	55 kg		
Dimensions LxWxH (mm)	489 x 340 x 435	535 x 380 x 487	650x453x660		
Packing Unit	1				

Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae

