



**Robin Machineries & Equipment**

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: [alawitra@emirates.net.ae](mailto:alawitra@emirates.net.ae)

[www.alawigroup.ae](http://www.alawigroup.ae)

### EG3800-A/EG3800D-A

- Rated power of 2800 watt, 110/220/230/240V
- Eagle commercial-grade OHV engine
- Automatic voltage regulation by AVR
- Low oil level automatic protection
- Current over current protection
- Capacious fuel tank of 18 liter, for which to run 13 hours constantly
- Frame-type safety generator support
- Wheel components are optional
- Self-starting or remote-starting is optional.



Engine model  
 Engine type  
 Power output  
 Bore×Stroke  
 Displacement  
 Compression ratio  
 Oil capacity  
 Fuel tank capacity  
 Fuel consumption  
 Continuing time  
 Rated frequency  
 Rated voltage  
 Voltage regulator system  
 Rated output  
 Max output  
 Power factor  
 Charging voltage  
 Charging current  
 Starting system  
 Ignition system  
 Noise (≤7m)  
 Dimension  
 Net weight

G240F/G240FD  
 Single cylinder,4stroke, forced cooling ,OHV  
 5.2Kw/3600rpm  
 73mm×58mm (2.9"×2.3")  
 242cc  
 8.2:1  
 0.6L (0.16gal)  
 18L (4.76gal)  
 ≤395g/Kw.h  
 13h  
 50 Hz/60 Hz  
 110V/115V/120V/220V/ 230V/240  
 Automatic Voltage Regulation  
 2.8Kw  
 3.1Kw  
 1.0  
 12V(DC)  
 8.3A(DC)  
 Recoil start/Electric-start  
 Transistorized magneto ignition  
 ≤76dB(A)  
 675×540×540 (26.6"×21.3"×21.3")  
 68Kg (150lb)

### Options:

- Fuel tank, recoil starter colors and types
- DC 12V output
- Voltage meter indicator type or digital type
- Wheel kit
- Intelligent Self-start or remote start