



Robin Machineries & Equipment

Tel: 000971-4-2217124
 Fax: 000971-4-2234493
 POBox: 5229 Dubai, UAE
 Email: alawitra@emirates.net.ae
www.alawigroup.ae

EG2500-A/EG2500D-A

- Rated power of 2000 watt, 110/220/230/240V
- Eagle commercial-grade OHV engine
- Automatic voltage regulation by AVR
- Low oil level automatic protection
- Current over current protection
- Capacious fuel tank of 18 liter, for which to run 15 hours constantly
- Frame-type safety generator support
- Wheel components are optional
- Self-starting or remote-starting is optional.



Engine model	G200F/G200FD
Engine type	Single cylinder, 4stroke, forced cooling ,OHV
Power output	4.1Kw/3600rpm
Bore×Stroke	68mm×54mm (2.7"×2.1")
Displacement	196cc
Compression ratio	8.5:1
Oil capacity	0.6L (0.16gal)
Fuel tank capacity	18L (4.76gal)
Fuel consumption	≤395g/Kw.h
Continuing time	15h
Rated frequency	50 Hz/60 Hz
Rated voltage	110V/115V/120V/220V/ 230V/240
Voltage regulator system	Automatic Voltage Regulation
Rated output	2.0Kw
Max output	2.2Kw
Power factor	1.0
Charging voltage	12V(DC)
Charging current	8.3A(DC)
Starting system	Recoil start/Electric-start
Ignition system	Transistorized magneto ignition
Noise (≤7m)	≤75dB(A)
Dimension	590×430×480 (23.2"×16.9"×18.9")
Net weight	43Kg (94.8lb)