

Other products



For Construction & Civil Engineering

**PONSTAR**

**PB Series**



PB-55011

### Powerful Pumps for Heavy Duties

- Double mechanical seals in oil chamber filled with liquid paraffin prevents damage from dry running.
- Liquid paraffin is used in the shaft seal. Water is not contaminated even in case of oil leakage.
- Thermal protector cuts off circuit in case of overload during operation.
- With automatic float switch. (PB-55022A)

### Specifications

Model		PB-55011	PB-55022	PB-65011	PB-68011
P	Connection Dia	50mm (2")			80mm (3")
U	Total Head	10 m (32 ft)			19 m (61 ft)
M	Delivery Volume	290 L/min (76 USG/min)			460 L/min (7286GPH)
P					
M	Voltage	AC 110 V	AC 220 V	AC 110 V	
O	Frequency	50 Hz		60 Hz	
T	Rated Current	7.3 A		8.7 A	28 A

O R	Output	400 W			1.5kW
	Consumption	760 W	680 W	750 W	1.8k W
	Revolution	2900 rpm		3400 rpm	
	Model	Induction Motor			
	Power Cord	10 m (32 ft) [CE Model], 6 m (19 ft)		6 m (19 ft)	13m (40 ft)
Standard Accesories		1 Rope (5m), 1 Hoseband			-
Gross Weight		32 kg	65 kg	35 kg	
Dimensions LxWxH (mm)		533 x 270 x 509	533 x 533 x 509	285 x 285 x 855	
Packing Unit		2	4	1	

**Robin Machinerics & Equipment**

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: [alawitra@emirates.net.ae](mailto:alawitra@emirates.net.ae)

[www.alawigroup.ae](http://www.alawigroup.ae)

