GAS LAWN MOWERS







• 12 steps is for central height adjustment. • 7 steps is for independent height adjustment.

Key Specification

| ITEM NO. | AM3050S2 | AM3050F1 | AM3050F2 | AM3050C2 | AM3050D1 | AM3050D2 | AM3050S6 | AM3051S1 | AM3051S2 | AM3051F1 | AM3051F2 | AM3051C2 | AM3051D1 | AM3051D |
|----------------------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Engine type | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 | 3.5 |
| Engine displacement (cc) | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 | 143 |
| Speed at max power (min*) | | 2500 | | 2500 | 2500 | 2500 | | 2500 | | 2500 | | 2500 | | 2500 |
| Self-propelled. RWD | N | N | N | N | N | N | N | N | Y | Y | Y | Y | Y | Y |
| Adjustable height position | 12 | 7 | 7 | 12 | 7 | 7 | 12 | 12 | 12 | 7 | 7 | 12 | 7 | 7 |
| Mulch plate insert. | N | N | N | N | N | N | N | N | N | N | N | N | N | N |
| Cutting width inch | 19* | 18" | 19" | 19" | 18" | 19" | 19" | 18" | 19" | 18" | 19* | 19* | 18* | 19" |
| Cutting width mm | 483 | 457 | 483 | 483 | 457 | 483 | 483 | 457 | 483 | 457 | 483 | 483 | 457 | 483 |
| Blade type | Standard | Standard | Standard | Standard | Standard | Standard | 2-Rotary | Standard |
| Grass collector type | Grass Box | Grass Box | Grass Box | Grass Bag | Grass Bag | Grass Bag | Grass Box | Grass Bag | Grass Bag | Grass Ba |
| Brake system | Y | Y | Y | Y | Y | Y | Y | Y | Y | Y | Y | Y | Y | Y |
| Sponge casing pipe | N | N | N | N | N | N | N | N | N | N | N | N | N | N |
| Drake adjuster | N | N | N | 19 | N | N | N. | N | N | N | N | N | N | N |
| Throttle adjuster | N | N | N | N | N | N | N | N | N | N | N | N | N | N |
| Self-propelled adjuster | N | N | N | N | N | N | N | Y | Y | Y | Y | Y | Y | Y |
| Wheel diameter Front | 6.5" | 6.5* | 6.5* | 6.5* | 6.5" | 6.5" | 6.5* | 6.5" | 6.5" | 6.5" | 6.5" | 6.5" | 6.5" | 6.5° |
| Wheel diameter Back | 6" | 8" | 8* | 8* | 8" | 8" | 8" | 8" | 8" | 8" | 8* | 8* | 8* | 8" |
| Cutting heights (High) inch | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"~3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" | 1"-3" |
| Cutting heights (High) mm | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 | 25.4-76.2 |
| Cutting heights (Low) inch | 0.6"-2.6" | 0.6"-2.6" | 0.6"-2.6" | 0.6"-2.6" | 0.6"-2.6" | 0.6*-2.6* | 0.6"-2.6" | 0.6"-2.6" | 0.6"-2.6" | 0.6"~2.6" | 0.6"-2.6" | 0.6*-2.6* | 0.6"-2.6" | 0.6"~2.6" |
| Cutting heights (Low) mm | 15-65 | 15-65 | 15-65 | 15-65 | 15-65 | 15~65 | 15-65 | 15~65 | 15~65 | 15-65 | 15-65 | 15-65 | 15-65 | 15~65 |
| Fuel tank (mil) | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 |
| Oil tank (mil) | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 |
| Grass collector capacity (Liter) | 53 | 53 | 53 | . 55 | 55 | 55 | 53 | 53 | 53 | 53 | 53 | 55 | 55 | 55 |
| Net weight Litro | 71.2 | 71.7 | 72.2 | 71.5 | 71.1 | 71.5 | 71.1 | 74.4 | 74.4 | 73.9 | 74.4 | 73.7 | 73.3 | 73.7 |
| Net weight Kg | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 | 33 |
| Certificates | GS/CE | GSICE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE |

GAS LAWN MOWERS





- Line of Lawn Mowers offers durability and maneuverability in a lightweight design.
- Equipped with rust resistant steel blades and wheels, these quality mowers are built to last.





Key Specification

• 12 steps is for central height adjustment. • 7 steps is for independent height adjustment.

| ITEM NO. | AM3052S1 | AM3052S2 | AM3052C1 | AIVI3052C2 | AM3053F1 | AM3053S1 | AM3053S2 | AM3053C1 | AM3053C2 |
|-----------------------------------------|-----------|-----------|-----------|------------|-----------|-----------|-----------|-----------|-----------|
| Engine type | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| Engine displacement (co) | 160 | 160 | 160 | 160 | 160 | 160 | 160 | 160 | 160 |
| Speed at max power (min ⁻¹) | 2500 | 2500 | 2500 | 2500 | 2500 | 2800 | 2800 | 2800 | 2800 |
| Self-propelled. RWD | N | N | N | N | . Y | Y | Y | Y | Υ |
| Adjustable height position | 12 | 12 | 12 | 12 | 7 . | 12 | 12 | 12 | 12 |
| Mulch plate insert | . N | N | N | N | N | N | N | N | N N |
| Cutting width inch | 18" | 19" | 18" | 19" | 18" | 18" | 19" | 18" | 19" |
| Cutting width mm | 457 | 483 | 457 | 483 | 457 | 457 | 483 | 457 | 483 |
| Blade type | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard | Standard |
| Grass collector type | Grass Box | Grass Box | Grass Bag | Grass Bag | Grass Box | Grass Box | Grass Box | Grass Bag | Grass Bag |
| Brake system | Y | Y | Y | Y | Y | Y | Y | Y | Y |
| Sponge casing pipe | Y | Y | Y | Y | Y | Y | Y | Y | Y |
| Brake adjuster | N | N | N | N | N | N | N | N | N |
| Throttle adjuster | N | N | N | N | N | N | N | N | N |
| Self-propelled adjuster | N | N | N | N | Y | Y | Y | Y | Υ |
| Wheel diameter Front | 6.5" | 6.5" | 6.5* | 6.5" | 8.5" | 6.5" | 6.5" | 6.5" | 6.5" |
| Wheel diameter Back | 8" | 8" | 8" | B" | 8" | 8" | 8" | 8" | 8" |
| Cutting heights (High) inch | 1"-3" | 1"~3" | 1"-3" | 1"~3" | 1"~3" | 1"~3" | 1"~3" | 1"~3" | 1"~3" |
| Outling heights (High) mm | 25.4-76.2 | 25.4~76.2 | 25.4-76.2 | 25.4~76.2 | 25.4-76.2 | 25.4-76.2 | 25.4~76.2 | 25.4~76.2 | 25.4-76.2 |
| Cutting heights (Low) inch | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" | 0.6"~2.6" |
| Gutting heights (Low) mm | 15-65 | 15~65 | 15~65 | 15~65 | 15-65 | 15~65 | 15~65 | 15~65 | 15~65 |
| Fuel tank (ml) | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 | 900 |
| Oil tank (mi) | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 | 594 |
| Grass collector capacity (Liter) | 53 | 53 | 55 | . 55 | 53 | 53 | 53 | 55 | 55 |
| Net weight Lbs | 76.1 | 76.6 | 75.5 | 75.9 | 78.3 | 78.3 | 78.8 | 77.7 | 78.1 |
| Net weight Kg | 39 | 39 | 39 | 39 | 39 | 39 | 39 | 39 | 39 |
| ertificates | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE | GS/CE |



Model: AM3051SP

Engine: Surefire[™] 4 Stroke

Cutting Width: 480mm

(19")

Cutting Height: 12 Position

Weight: 38kg

Catcher 500ml Bottle of SAE30 Engine Oil

Talon Self Propelled

Featuring the new Talon Surefire four stroke engine, self propelled rear wheel drive system, a 480mm steel deck with single lever 12 position height adjustment, 53 Litre catcher, cutting disc and two swing back blades.







Engine: Surefire[™] 4 Stroke

Cutting Width: 480mm

(19")

Cutting Height: 15mm to

66mm

Weight: 38kg

Catcher 500ml Bottle of SAE30 Engine Oil

Talon Super Cut & Catch

Talon Eagle Super cut and catch lawn mower with Surefire 4 stroke motor. Features unique and patented soft grip folding top handle section, high air intake and easy to use speed control, PLUS 200mm cast aluminium ball bearing wheels. With a 480mm steel deck, single lever 12 position height adjustment, 53 Litre catcher, cutting disc and four swing back blades.







Engine: Optiva 550 Over

Head Valve

Cutting Width: 480mm

(- -)

Cutting Height: 15mm to

66mm

Weight: 38kg

Catcher 500ml Bottle of SAE30 Engine Oil Mulching Plug

Talon Ultimate Mulch or Catch

Talon Eagle Ultimate Mulch or Catch lawn mower with high power Optiva 550 four stroke overhead valve motor. Features unique and patented soft grip folding top handle section, high air intake and easy to use speed control, PLUS 200mm cast aluminium ball bearing wheels. With a 480mm steel deck, single lever 12 position height adjustment and catcher. Cutting disc and four swing back blades.





Model: AM201816C

Cutting Width: 40cm

Height Adjustment: 6 adjustable position

Catcher

Hand Push Reel Mower

40cm Hand Push Reel Mower with 6 adjustable height settings. Complete with catcher.





Motor: 1500Watt (TBC)

Cutting Width: 350mm

(14")

Height Adjustment:

Single Lever 6 Position

Blades: Single bar

Weight: 25kg

Plastic catcher

Talon Electric Cut & Catch

Talon Eagle electric cut and catch lawn mower features single lever adjustable height, solid catcher and a powerful 1500 watt motor.





Motor: Talon Surefire 145 4

Stroke

Cutting Width: 460mm

(18'')

Blades: Swing Back Blade

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

55mm

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

35kg

Plastic Catcher

500ml bottle of SAE30 oil

Talon Cut & Catch

Talon cut and catch lawn mower with four stroke motor. Features 460mm cutting path, 10 position single lever height adjustment and solid plastic catcher.





Motor: High Power Talon Optiva 550 OHV 4 Stroke

Engine

Cutting Width: 480mm

Height Adjustment:

Single Level 12 Position

Cutting Height: 15mm to

66mm

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Catcher

500ml bottle of SAE30 oil

Harrier Mach 559

Harrier Mach 559 Cut & Catch Lawn Mower with Optiva 550 overhead valve four stroke engine, four swing back blades, 480mm cutting width, ball bearing wheels, 12 position single lever height adjustment and large capacity catcher. 500ml bottle of SAE 30 oil included.





Model: AM3010KS

Motor: Talon Surefire 145

4 Stroke

Cutting Width: 460mm

(18'')

Blades: Swing Back Blade

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

Cutting H 65mm

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

weign 38kg

Key Start: 12 Volt NiCad

Battery Pack

45 litre Plastic Catcher 500ml bottle of SAE30

engine oil

Power Eagle Key Start

Talon cut and catch lawn mower with four stroke motor. Features 12 Volt NiCad Battery Key Start, 460mm cutting path, 10 position single lever height adjustment and solid plastic catcher.





Motor: Talon Surefire 145

4 Stroke

Cutting Width: 460mm

(18")

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

65mm

Blades: 2 Swing Back

Blades

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

35kg

Plastic Catcher

500ml bottle of SAE30 oil

Hawk Cut & Catch

Talon cut and catch lawn mower with four stroke motor. Features 460mm cutting path, 10 position single lever height adjustment ball bearing wheels and solid plastic catcher.





Motor: Talon Surefire 145

4 Stroke

(18")

Cutting Width: 460mm

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

65mm

Blades: 4 Swing Back Blade

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

35kg

Plastic Catcher 500ml bottle of SAE30 oil Mulching Insert

Hawk Mulch or Catch

Hawk Mulch or Catch Lawn Mower with Surefire 145 four stroke engine, mulching insert, four swing back blades, 460mm cutting width, ball bearing wheels, 10 position single lever height adjustment and large capacity catcher. 500ml bottle of SAE 30 oil included.





Motor: Talon Surefire 145

4 Stroke

Cutting Width: 460mm

(18'')

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

66mm

Blades: 4 Swing Back

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

38kg

Catcher 500ml bottle of SAE30 oil

Falcon 460 Cut & Catch

Falcon 460 Cut & Catch Lawn Mower with Surefire 145 four stroke engine with above deck oil change tap, high intake air filter, four swing back blades, 460mm cutting width, 10 position single lever height adjustment and large capacity catcher. 500ml bottle of SAE 30 oil included.





Motor: Talon Surefire 145

4 Stroke

Cutting Width: 460mm

(18")

Height Adjustment:

Single Level 10 Position

Cutting Height: 15mm to

65mm

Blades: 2 Swing Back

Blades

Fuel Tank Capacity:

900ml

Oil Tank Capacity: 500ml

Wheel Size: 165/200mm

Weight Incl. Catcher:

35kg

Plastic Catcher

500ml bottle of SAE30 oil

Silver Eagle Cut & Catch

Silver Eagle Cut & Catch Lawn Mower with Surefire 145 four stroke engine, high zone starting, swing back blades, 460mm cutting width, 200mm wheels, 10 position single lever height adjustment and large capacity catcher. 500ml bottle of SAE 30 oil included.





Robin Machineries & Equipment

Tel: 000971-4-2217124 Fax: 000971-4-2234493 POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae